

# Exit Device Nomenclatures

The chart below provides a quick cross reference guide of simplified dormakaba exit device nomenclatures. Where noted, the option has become the standard for the respective exist device nomenclature.

Option Description	Previous Nomenclature:	New Nomenclature:
Batt powered alarm	BPA	BA
Batt powered alarm 4 min reset	BPAR	B4
Direct wire alarm	DWA	DA
Pullman btm latch	PB	P
Slide bolt (default) (btm latch)	SB	Default Nomenclature Feature
Flat slide bolt btm str	340	F
Recessed btm str pullman	431	P
Standard slide blt btm str	439	Default Nomenclature Feature
Surf BTM strike pullman	416V	R
DE CBC	DCBC	R
DE 30 second	DE30	D3
ELR w/battery	ESB	EB
Metric fasteners	METRIC	M
Shim Kit	SK	S
SK & TX	SKTX	ST
SK & TX & SNB	SKTXSNB	BST
Security Screws	TX	T
Latch bolt and touchbar switch	LMMS	LT
Bolt & bar switch w/bypass	LMMSBP	BP
Std mort str	465	Default Nomenclature Feature
Mort open back str	565	O
Rim overlap strike	320	V
Rim box strike	430	B
Std rim str	463	Default Nomenclature Feature
Roller str	486	R

Option Description	Previous Nomenclature:	New Nomenclature:
Standard top strike	418	Default Nomenclature Feature
Wood frame top strike	419	W
Standard top strike	426	Default Nomenclature Feature
Top strike w/angle	426A	A
Mort elec fail safe	LFSF	EL
Mort elec fail secure	LFSC	EU
Aluminum door bracket	ALD	A
7ft top rod	7FT	7
8ft top rod	8FT	8
9ft top rod	9FT	9
10ft top rod	10FT	10
689 device w 630 Touchbar	689630TB	689630