

Kaba registration unit 90 02



Advantages at a glance

Elegant design
Innovative product design
in a compact structure

Robust and durable
Suitable for outdoor use

Easy to operate
Intuitive operation thanks to
Guide by Light

Easy to install
Quick 1-Click installation
thanks to the quickwire
technology

Tamper-proof
High security thanks to the
control unit installed in secure
internal areas

Secure in the future
Ready for use with Mobile access

The reliable access solution with keypad

The Kaba registration unit 90 02 offers an integrated keypad for access systems, providing flexible use for high security requirements. The registration unit is typically positioned away from the control unit. Regardless of the installation location, the accompanying Kaba control unit can be installed in a tamper-proof area.

Elegant and practical

The scratch-resistant glass surface, wearfree keys, aesthetic design and complete product portfolio also safeguard your investment in the case of intensive usage over a long operating period.

Flexible installation

With the innovative quickwire technology, installation is quick and efficient.

Function

The registration unit is fitted with an RFID interface and keypad to enable employees to be identified. The light symbol and acoustic signal generator inform the user if access has been granted or denied. Keypad operation is supported by Guide by Light.

Areas of application

The Kaba registration unit 90 02 is suitable for access points that require additional PIN verification for security reasons. It is designed for adverse operating conditions and can be used in both inside and outside.



Product specification

Innovative product design

The registration unit possesses an innovative design, comprising a silver frame and a high-gloss black front.

User prompting

An acoustic signal and a light symbol (green/red) indicate whether access has been granted or denied. Access media are held up to the light symbol. If PIN entry is requested, the keypad will light up. Users are thereby assisted by Guide by Light.

Installation

The registration unit can be installed on various surfaces, including directly onto metal, in internal and protected external areas. It is designed for surface cable mounting using a spacer frame and flush cable mounting using a rear panel. This allows the registration unit to be installed directly onto the wall or using a flush mounting box. The quickwire technology makes installation quick and secure.

quickwire technology


With the state-of-the-art quickwire technology, the entire wiring is separated from the electronics in the rear panel or spacer frame. The electronics are only clicked into the unit when it is commissioned – a practical concept that makes installation easier (1-Click installation).

Compatibility

The Kaba registration unit 90 02 operates using the following Kaba control devices:

- Kaba access manager 92 00
- Kaba remote reader 91 15
- Kaba remote reader 91 25

Remark: The effective functions available of the product depend on the system context in which it is used.



Technical features

Terminal

- communication via 50 Ω coaxial cable (RG 174/U recommended)

Environmental conditions

- temperature: -25°C to +70°C
- humidity: 0 to 95%, non-condensing
- protection class: IP54 (with rear panel & sealingmat) IP40 (with spacer frame)

Design / material

- rear panel/spacer frame: material: PC/ABS colour: RAL 9005 (black) RAL 9016 (white)
- frame: material: PC/ABS colour: RAL 9006, NCS S2502-B
- front: material: autotex polyester film in PMMA colour: RAL 9005 (black) RAL 9016 (white)

Dimensions

- with rear panel: 88.5 x 88.5 x 19.4 mm (W x H x D)
- with spacer frame: 88.5 x 88.5 x 26.4 mm (W x H x D)

Certificates / standards

- EN 301 489-1, EN 301 489-3, EN 300 330-1, EN 300 330-2
- R&TTE 1999/5/EC

Further details and order information can be found in the relevant Kaba catalogues or system descriptions.



Certified Management System, ISO 9001