



Product Information

DORMA-Glas GmbH
herewith certifies
that the product

MUNDUS Comfort Patch Fitting PT10, PT20 und PT 30

has been tested in a durability test according to DIN EN 1154.

This was done in an exemplary test series:
The fittings were mounted on a glass door with 150 kg weight

The following standards have been met for the product through the test series:

- Life cycle: 500.000 cycles
- max. door width: 1.100mm
- max. door height: 2.000mm
- max. System height: 3.000mm (incl. over panel)
- max. System width: 4.000mm (incl. side panel)
- Glass thicknesses: 8 to 12mm
- Glass type: TSG
- Glass surface: clear, satined, no using of Self-cleaning surfaces

For doors with more than 80kg weight please use a door closer type EN4 (with or without back check) or a higher type EN5 WITHOUT back check.

For glass panels with a panel height of more than 2.500mm and a glass thickness \leq 10mm following limiting condition applies:

Use of pull handles with a length of at least 2/3 of the total panel height and with at least 3 fixing points are prescribed.

Corrosion Resistance:

- Test according to EN1670:2008
- Test Result → Grade 4 (240h according ISO 9227)

Temperature range: -10° C to +70° C

DORMA-Glas GmbH
Max-Planck-Str. 33-45
D-32107 Bad Salzufflen

25. July 2016