





	Model	Order No.
<b>NT Power supplies</b>		
	NT-12 VDC, 5 A Power supply for DIN-rail mounting <b>NT-12 5, 12V DC</b>	56125200
56125200		
56125100	NT-24 VDC, 2,5 A Power supply for DIN-rail mounting <b>NT-24 5, 24V DC</b>	56125100
<b>USV Power supplies</b>		
	USV-12 VDC, 5 A Power supply with battery management for DIN-rail mounting <b>USV-12 5, 12V DC with battery management</b>	56125250
56125250		
56125150	USV-24 VDC, 3 A Power supply with battery management for DIN-rail mounting <b>USV-24 3, 24V DC with battery management</b>	56125150
<b>NT-G Housing for power supplies</b>		
	Steel housings with DIN-Rail for power supply NT or USV and battery pack AP 1224. degree of protection: IP class 30, with cover contacts, lockable via Euro-profile half cylinder (by others) according to DIN standard 18 252. Maximum 4 batteries AP 1224 can be fixed in the housing Dimensions (W x H x D) approx.: 305 x 380 x 126 mm, Operating voltage 230V AC.	
56126300	<b>NT-G housings with DIN-rail, lockable</b>	56126300
<b>AP 1224 Battery pack</b>		
	Plug-in connected emergency supply, 30 V/3.0 Ah for USV-12 5 and USV-24 3, to maintain operation of emergency exit or door security system in the event of power failure or, voltage dip. 2 or 4 pieces are needed in combination with USV 24-3. 1 or 2 pieces are needed in combination with USV 12-5	
56622400	<b>AP 1224 Battery pack</b>	56622400
<b>Accessories for Power supplies</b>		
	Cable set to connect maximum 2 battery packs to USV-12 Power supply	
	<b>Cable set 12V</b>	56622401
	Cable set to connect 2 or 4 battery packs to USV-24 Power supply	
	<b>Cable set 24V</b>	56622402