

HZ 43-F

Product features

- automatic flush bolt
- detachable split spindle
- spring-loaded latch
- for timber and profile doors
- LH/RH versions available
- suited for use in smoke and fire protection doors
- installation on top and bottom of the inactive door leaf possible

Benefits

- automatic locking and unlocking of the inactive door leaf
- less mounting effort through split spindle:
 - plug-in connection without additional bolting
 - only one cutout for lock case / one screw hole for latch bolt necessary
 - corner of the door leaf does not have to be removed or cut open, the doors stability remains intact
- compensation of mounting tolerances and enhanced operational reliability:
 - angled latch bolt
 - adjustable latch bolt length
 - Spindle flexible mounted
 - adjustable locking plate unit



HZ 43-F description text

locking solution for double doors, suited for fire and smoke doors with automatic door coordinators e.g. automatic door operator DORMA ED 100/250. The inactive leaf is automatically being released once the active leaf is ajar, upon closure of the active leaf the inactive leaf gets locked automatically. Split spindle facilitates mounting and enhances flexibility.

Shipments includes HZ 43-F flush bolt, guide tube, locking plate unit und strike plate

HZ 43-F

	Article-no.	
HZ 43-F22 DIN-L	15199002	
HZ 43-F22 DIN-R	15199003	

