


Raccordement du verrouillage EM


Sélection tension

F


Relais Verrouillage

Alimentation 12 ou 24 V DC

12 V DC 24 V DC (réglage usine)



Contact de verrouillage

Le contact du relais est fermé si le verrouillage EM est alimenté et la contreplaque est correctement en place.

LED intégrée

LED éteinte: Pas d'alimentation

LED rouge fixe: Pas verrouillée

LED verte : Verrouillée

Caractéristiques techniques

 Alimentation: 12 ou 24 V DC
+20% / -10%

 Consommation X 2: 500 mA en 12 V DC
250 mA en 24 V DC

Protection: Par VARISTOR intégrés


Contact relais: Max 24 V DC et 2000 mA



Circuits sensibles à l'électricité statique

Electromagnet connections


Voltage selection

GB


Door locked contacts

Power supply 12 or 24 V DC

12 V DC 24 V DC (factory setting)



Door locked contact

The door locked contact is closed if the electromagnet is powered and if the armature plate is correctly in place.

Integrated LED

LED off: No power supply

LED red: Unlocked

LED green: Locked

Technical data

 Power supply: 12 or 24 V DC
+20% / -10%

 Current input X 2: 500 mA with 12 V DC
250 mA with 24 V DC

Protection: By integrated VARISTOR

Contact relay: Max 24 V DC and 2000 mA



Static sensitive devices