


Raccordement du verrouillage EM



Relais Verrouillage

Alimentation 12 ou 24 V DC

Contact de verrouillage

Le contact du relais est fermé si le verrouillage EM est alimenté et la contreplaque est correctement en place.

LED intégrée


LED éteinte: Pas d'alimentation

LED rouge fixe: Pas verrouillée

LED verte : Verrouillée

Sélection tension

12 V DC 24 V DC (réglage usine)



Caractéristiques techniques

Alimentation: 12 ou 24 V DC
+20% / -10%

Consommation: 500 mA en 12 V DC
250 mA en 24 V DC

Protection: Par VARISTOR intégrés


Contact relais: Max 24 V DC et 2000 mA



Circuits sensibles à l'électricité statique

F

Electromagnet connections



Door locked contacts

Power supply 12 or 24 V DC

Door locked contact

The door locked contact is closed if the electromagnet is powered and if the armature plate is correctly in place.

Integrated LED


LED off: No power supply

LED red: Unlocked

LED green: Locked

Voltage selection

12 V DC 24 V DC (factory setting)



Technical data

Power supply: 12 or 24 V DC
+20% / -10%

Current input: 500 mA with 12 V DC
250 mA with 24 V DC

Protection: By integrated VARISTOR

Contact: Max 24 V DC and 2000 mA



Static sensitive devices

GB