



1. The ED100 & ED 250 Double Egress package consists of:
 - A. Operator:
 - ED100 LE / FE door leaf:
 - Maximum 43" [1092] wide, 220 lbs [100].
 - ED250 LE door leaf:
 - Maximum 38" [965] wide at 265 lbs [120].
 - Maximum 46" [1168] wide at 165 lbs [75].
 - ED250 FE door leaf:
 - Maximum 55" [1400] wide at 550 lbs [250].
 - Maximum 63" [1600] wide at 420 lbs [190].
 - Operator is NOT handed, can be Left or Right.
 - B. Standard Cover length at 27" [686] extruded aluminum with plastic endcaps.
 - C. Arm Kit:
 - Push arm reveal = 0" to 8 3/4" [222] Max.
 - Deep pull arm reveal = 0" to 2 1/4" [57] Max.
 - System reveal = 0" to 2 1/4" [57] Max.
 - 1 3/16" [30] axle extension kit.
 - D. Connection Kit:
 - #14 x 2-1/2" Phillips Flat Head Wood Screws.
 - #14 x 1-1/4" Phillips Flat Head Self Drilling Screws.
 - #12 x 1 1/2" pan head wood screws to mount shoe.
 - M6 x 1 x 20mm pan head machine screws to mount shoe.
 - #8 x 1-3/4" SPAX pan head wood screws to mount track.
 - M5 x 0.8 x 30mm pan head machine screws to mount track.
 - E. Required ANSI labels.
2. Finishes:
 - A. Extruded Cover:
 - Clear (BHMA 204) or Dark Bronze (BHMA 313) anodized finish (Standard).
 - Custom painted.
 - Custom anodized.
 - Cladding.
 - B. Endcaps:
 - Silver or black painted.
 - C. Arms:
 - Silver or black painted.
3. Typical Package Options:
 - A. Professional cover (pair) 56" [1422] to 125" [3175].
 - B. dormakaba Upgrade cards. (See brochure for details).
 - FE upgrade card.
 - Fire Protection upgrade card.
 - Professional upgrade card.
 - Barrier-Free Toilet upgrade card.
 - C. Vario Cover Kit (a pair cover made with 2 singles) (see options page).
 - D. Axle extensions (See chart for available lengths).
4. Drawing Notes:
 - A. Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
 - B. Operator dimensions:
 - Width x Height x Depth: 27" [686] x 2 3/4" [70] x 5 1/8" [130].
 - Operator weight: 26.5 lb [12 kg].
 - C. Maximum opening angle of 110°.
 - D. See installation manual for further details.
5. Power Requirements:
 - A. 120V +/- 10%, 50/60 Hz, 6.6A peak (per operator). Service to header by electrician.
6. Standards of Compliance:
 - A. UL 325 & CSA 22.2 (listed with ETL).
 - B. Designed to comply with these standards depending on installation and application:
 - International Building Code (Section 1008).
 - ANSI/ BHMA 156.10 (Requires additional overhead activation and safety sensors) (May also require guide rails depending on configuration).
 - ANSI/ BHMA 156.19 (Requires additional knowing activation devices not shown in drawing).
 - NFPA 101 Life Safety Code (Section 7.2.1.9).
 - C. Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
 - D. Tested to UL 10B 90 min. fire rated door assembly.
7. Contact dormakaba Architectural Services for more information:
 - A. Phone: 1-844-SPEC-NOW (1-844-773-2669)

PULL AXLE EXTENSION	PULL AXLE DISTANCE	PUSH AXLE EXTENSION	PUSH SHOE HEIGHT	PUSH ARM CLEARANCE	
FLUSH	9/16" [14]	1 3/16" [30]	2 11/16" [69]	1 3/4" [44]	STANDARD (SHOWN)
1 3/16" [30]	1 3/4" [44]	2 3/8" [60]	3 7/8" [99]	2 15/16" [74]	
2 3/8" [60]	2 15/16" [74]	3 9/16" [90]	5 1/16" [129]	4 1/8" [104]	FOR ED250 ONLY