

Date: 02/20/2017

Product: LA GARD Backlit Input Unit

Subject: New LA GARD Models 5715, 5750, and 5750-K Input Units

Bulletin #28

The new LA GARD Model 5715, 5750, and 5750-K Input units for use with LA GARD locks have been released into production. These new input units are intended as replacements for retiring models 4715, 3750, and 3750-K, respectively. These retiring models will be discontinued when inventory is depleted, with a target End-Of-Life in mid-2017.

The new 57xx series of input units are a drop-in replacement for those models being retired. There will be no price difference between the new 57xx keypads and their corresponding retiring models.



Model 5715



Model 5750

New Features:

- All 57xx models come with a backlit keypad as a standard feature.
- All 57xx models come with a two-year warranty from date of manufacture.
- All 57xx models have withstood unprecedented Reliability Life Cycle testing performed by industry leading international Quality Assurance test lab.

Other Features and Benefits Include:

- Lock Firmware compatibility

| | 5715 | 5750 | 5750-K |
|---|------|------|--------|
| Basic/Basic Plus 4200/4200M, 3740, 3734 | ✓ | ✓ | ✓ |
| ComboGard Pro 4300/4300M, 6040/6040M, 6034, 6441 Redundant | ✓ | ✓ | ✓ |
| AuditGard 4300/4300M, 6040/6040M, 6034, 6441 Redundant | | | ✓ |

NOTE: Locks retain all current UL and VdS/EN 1300 certifications when paired with 57xx input units as shown in this table.

- 57xx are offered in the following finishes:
 - 5715-SC Satin Chrome
 - 5715-BC Bright Chrome
 - 5715-BK Black
 - 5715-BN Black Nickel
 - 5750-SC Satin Chrome
 - 5750K-SC Satin Chrome
- Single nine-volt battery, accessible from the outside of the locked container.
- Hinged battery door on the 5750 and 5750-K for ease of battery replacement.
- Improved keypad button response with Direct-Press circuit board contact
- Improved keypad membrane
- Improved PCBA manufacturing and reliability
- For spindle models, easy-twist design with improved grip points
- Improved wire routing for cable retention
- Standard vertical mounting points; consistent installation, compatibility, and function with LA GARD locks, accessories, and industry standard dimensions

New documents being released with the 57xx keypads:

- 7030.0316 5715 User Operating Instructions
- 7031.0316 5750 User Operating Instructions
- 7032.0316 5750-K User Operating Instructions
- 732.018 Rev O ComboGard Manager Instructions
- 759.128 Rev F AuditGard Manager Instructions
- 762.128 Rev G Entry device installation instructions