

**DATA SHEET**

**KEY CARD SWITCH**

**Hartland CFX Satin Steel 1 gang On/Off 10A (6AX) Card Switch with Blue LED Locator. Standard Insert will be Satin Steel with a Black surround.**

<b>Plate Information</b>	
Plate Finish	Satin Stainless
Switch Colour	Satin Stainless
Body & Switch Trim	Black or White
Dimensions	H: 86mm x W: 86mm x D: 5mm
Fixing Hole Centres	60.3mm
Minumum Wall Depth	35mm
<b>Technical Information</b>	
Current Rating	10A (6AX)
Max Load	10 Amp (6 Amp inductive)
Voltage	220/250V AC
IP Rating	IP2XD
Switched Poles	Single
Contact Gap Minimum	3mm
Product Class 1	Faceplate must be earthed
Ambient Operating Temperature	-5° to +40°C
Location	Internal Use Only
Max Installation Altitude	2000m
<b>Standards</b>	
BS EN ISO Standard	BS EN 60669-2-3



**DATA SHEET**

**Terminal Capacity**

	1mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup> Multi-Strand	6mm <sup>2</sup>
Terminal Capacity	3	2	1		
Earth Terminal Capacity	5	4	3	1	1

**Head Office**  
**Kaba Ltd**, Lower Moor Way, Tiverton Industrial Estate,  
 Tiverton, Devon EX16 6SS  
 Tel.: +44(0) 870 000 5625  
 Fax: +44(0) 870 000 5397  
 info@kaba.co.uk www.kaba.co.uk

**London Office**  
**Kaba Ltd**, Unit 27, Bates Industrial Estate, Harold Wood,  
 Romford, Essex, RM3 0HU  
 Tel.: +44(0) 870 000 5292  
 Fax: +44(0) 870 000 5293  
 info@kaba.co.uk www.kaba.co.uk