

# RCI 3525

Electromechanical rack handle lock

# RCI 3525PRX

With proximity reader



3525



3525PRX

## Providing intelligent electronic locking and monitoring capabilities.

### Common Features

- Easy to install and use
- Local monitoring with multi-color LED indicator
- Remote lock and unlock control
- Single or multi-point locking
- Low power, gear motor driven mechanism
- Momentary or continuous lock actuation
- High security DIN lock for mechanical key override
- Non-handed – for use with right and left handed doors
- Wire harness and hardware kit included
- Includes three keys (keyed alike)
- Activated via any third party control system (Access Control)
- Housing, handle and mounting bracket are made of black, glass-filled nylon
- Shaft and rotation limiter are made of die-cast zinc with a bright sealer finishing

### 3525PRX Model Includes

- 125kHz HID® reader recognizes existing employee RFID prox cards
- Wiegand output can be connected to a standalone controller or an existing networked access control system for remote control, monitoring and reporting



Energy  
12-24VDC



Warranty  
1 Year Limited  
Warranty



Proximity  
Built-In 125kHz  
HID® Proximity  
Reader (3525PRX)



PoE  
PoE Power  
Friendly



Monitoring  
Lock & Handle  
Status



### Dimensions


#### 3525

1-1/2"W x 6-3/4"H x 1"D  
(37mm x 170mm x 24.5mm)

#### 3525PRX

1-1/2"W x 8-1/4"H x 1"D  
(37mm x 210mm x 24.5mm)

### Opening Dimensions



Door


## Accessories

### Cams



Cam	Grip	Length
3525-GR3815	0.61" (15.5mm)	1-1/2" (38mm)
3525-GR3817	0.69" (17.5mm)	
3525-GR3819	0.77" (19.5mm)	
3525-GR3821	0.85" (21.5mm)	
3525-GR3823	0.93" (23.5mm)	1-3/4" (45mm)
3525-GR4522	0.77" (19.5mm)	
3525-GR4524	0.85" (21.5mm)	
3525-GR4526	0.93" (23.5mm)	

**Note:** For grip ranges .61"-.73" (15.5-18.5mm), max. cam length of 1.5" (38mm), frame edge distance of 1.18" (30mm). For grip ranges greater than .73" (18.5mm), max. cam length of 1.77" (45mm), frame edge distance of 1.46" (37mm). For multipoint systems, select right or left hand gear box part number from table.



### Cards & Fobs

1326R-H – 125kHz Proximity Card (Clamshell)

**Note:** Sold in packs of 10, 25 & 50

### Gearboxes for Multi-point Systems



3525-MPLH – Left Hand Gearbox (CCW to open)

3525-MPRH – Right Hand Gearbox (CW to open)

Model	Volts	Amps*
3525	12-24VDC	Less than 200mA at 12VDC
3525PRX		

\*Operating Current

Typical: less than 200mA at 12VDC, max/stall: 1A, standby: 50mA max, output signal: 100mA max load, card reader module: 60mA max.

HID is a registered trademark of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners. RCI reserves the right to change specifications without notice.

© dormakaba 2019 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation. Printed in Canada.

dormakaba Canada Inc.  
65 Struck Court  
Cambridge, Ontario  
Canada N1R 8L2  
1-800-265-6630  
sales\_RCI@dormakaba.com  
dormakaba.us

ZL3525-0219